



12.1" POS TFT LCD Monitor



LP-12Rxx

Viewing Area	12.1" TFT	
Resoluton	800 x 600 SVGA	
Effective display area	246 x184.5(mm)	
Color	262,144	
Response time(tr/tf)	15/30ms	
Contrast ratio	300:1	
Brightness	160 cd/m2	
View angle	90°X(H) / 40°X(V)	
VGA Signal	Analog VGA	
Scan frequency	H:31.5~48 KHz / V:56~72 Hz	
Composite Signal(VIDEO)	-	
Control	Brightness, Contrast, H-Phase, V-Phase, Size....	
Adaptor	Universal AC 100 ~ 240 V, 50 / 60 Hz / DC +12 V	
Consumption(Max)	15W	
Temperature	0°X ~ 50°XC	
Humidity	10% ~ 85%	
Dimension	302(w) X 287.5(H) X 160.3(D)	
Weight	2.2Kgs	
Safety & EMI	FCCB,ETL,ETLC,CE,TUV/GS	
Audio	-	
Optional	Touch Panel	Chiling Resistive (4 Wires) or 3M Resistive (8 Wires) or ELO Resistive (5 Wires)
	Glass	Anti-Reflection Strengthen Glass
	Card Reader	300,000 Pass or 1,000,000 Pass
	Cabiet Color	White or Black

